





power



PHONES



EQ OUT



50Hz 200Hz 800Hz 3.2kHz 12.8kHz

equalizer



1 SYSTEM 2 SPEAKERS



EQ DEFEAT



SUBSONIC FILTERS



9kHz FILTERS

marantz

DC AMPLIFIER / MOVING COIL PHONO

LEFT

RIGHT

POWER LEVEL (WATTS)

100	50	3	0.1	0.005	8Ω	0.005	0.1	3	50	100
200	100	6	0.2	0.01	4Ω	0.01	0.2	6	100	200

12.8kHz

EQ DEFEAT SUBSONIC FILTERS 9kHz LOUDNESS MONO 1 TAPE MONITOR 2 TAPE MONITOR

console stereo amplifier *PM 551 DC*

2 - PHONO - 1
MM
MM
MC
TUNER
TAPE 3
/AUX



selector



volume

COPY DIRECT
1-2
2-1
PHONO
TUNER
TAPE 3
/AUX



record out



LEFT RIGHT

balance



2
MONITOR

SYSTEM 1
SYSTEM 2
SYSTEM 1

R L

PHONO 1
MM

PHONO 2
MM/MC

INPUTS

TUNER

TAPE 3
/AUX

R L

R L

IN

TAPE 1
MONITOR

OUT

IN

TAPE 2
MONITOR

OUT

R L

GND

F 13
SERIA

SYSTEM 1 : 4 ~ 16 OHMS
SYSTEM 2 : 4 ~ 16 OHMS
SYSTEM 1+2 : 8 ~ 16 OHMS

SPEAKER SYSTEMS

SYSTEM 2 SYSTEM 1

— R — — L — — R — — L —

+ - - + + - - +

VOLTAGE SELECTOR

240V 120V
220V 110V

FTZ
13/618S

MODEL NO. PM 5500c
110/120/220/240V ~ 50Hz

MADE IN JAPAN

SERIAL NO.

105131563

CAUTION: FOR CONTINUED PROTECTION
AGAINST FIRE HAZARD, REPLACE ONLY
WITH SAME TYPE FUSE. 110V/120V ~
T 3.5 A, 220V/240V ~ T 1.25 A.



SYSTEM 1 4 ~ 16 OHMS
SYSTEM 2 4 ~ 16 OHMS
SYSTEM 1 + 2 8 ~ 16 OHMS

SPEAKER SYSTEMS
SYSTEM 2 SYSTEM 1
R L R L

VOLTAGE SELECTOR
240V 120V
200V 110V

R L PHONO 1 MM
R L PHONO 2 MM/MC
INPUTS
R L TUNER
R L TAPE B JALK
R L IN TAPE 1 MONITOR
R L OUT
R L IN TAPE B MONITOR
R L OUT

FTZ 13-6185
STEREO AMPLIFIER
MODEL NO. PM 85000
110/220/240V ~ 50Hz
SERIAL NO. 135131603

CAUTION: THE CONTINUED PROTECTION AGAINST FIRE HAZARD. REPLACE ONLY WITH SAME TYPE FUSE. 110V/120V ~ 1.5A. 220V/240V ~ 1.12A.