



ALTEC LANSING P522B POWER SUPPLY

PARTS LIST

Part No.	Description
V1, 2	6X4
T1	PEERLESS 6001
C1	125 MFD. 350V. MALLORY FP-140
C2,3&C4,5	80X80 MFD. 300V. CD-UP8830
C6	10MFD, 150V. CD-BR1015
R1	100 OHMS 10W. OHMITE B.D.
R2,3,4	100 " 2 W.
R5	150,000 OHMS 1W.
R6	47,000 " "
J1	CANNON DA-15-34P

J1 PIN CONNECTIONS

- 1,2 } 117 V.A.C. 50-60 ~
- 3,4 } HEATER
- 5 } HEATER
- 6 } 6.3 V.A.C. AT 4.9 AMP
- 7 } HEATER
- 8 } BIASED +65 V.D.C.
- 9 } CHASSIS GROUND
- 10 } CHASSIS GROUND
- 11 } CIRCUIT GROUND
- 12 } CIRCUIT GROUND
- 14 } + 250 V. AT 65 MA. MAX.) CONDITION 1 *
- 15 } + 270 V. AT 75 MA. MAX.)
- 15 } + 270 V. AT 135 MA. MAX. - CONDITION 2 *

* CONNECTED LOAD 135 MA. MAX.