

A R T I S T

 Cabasse

To the heights of *e*motion

# ARTIS

THE NEW ARTIS RANGE, FRUIT OF A TEAM PASSIONATE ABOUT MUSIC AND ITS REPRODUCTION, COMBINES THE LATEST CABASSE'S INNOVATIONS IN CO-AXIAL DRIVERS WITH "CUTTING-EDGE" RESEARCH IN CABINETS' DAMPENING. CREATED TO OPTIMISE THE MUSICAL QUALITIES OF THE NEW CO-AXIAL DRIVERS, THE TC22 AND BC13, THE ARTIS RANGE BRINGS ELEGANCE AND PURITY OF SOUND INTO YOUR HOME. THE CABASSE ARTIS RANGE, THE LEGEND CONTINUES...



EGEA II

IROISE II

THOR II ARTIS

AMBROSE II

# T I S



BALTIC II

KARA

*Tweeter:*  
3,000 – 22,000 Hz  
*Midrange:*  
500 – 5,000 Hz  
*Low-midrange:*  
80 – 1,000 Hz



## TC22 DRIVER

The new 3-way co-axial large bandwidth unit  
SCS\* Technology

Frequency response: 80 – 22,000 Hz

*\* Spatially Coherent Source*

*Tweeter:*  
3,000 – 22,000 Hz  
*Midrange:*  
500 – 5,000 Hz



## BC13 DRIVER

2-way co-axial midrange-tweeter  
SCS\* Technology

Frequency response: 500 – 22,000 Hz

*\* Spatially Coherent Source*



## GLOBAL DAMPENING SYSTEM®

A new hi-tech concept from Cabasse designed to optimise the acoustical neutrality of the cabinet's structure.

To the heights of this concept:  
Ambrose II, Egea II, Iroise II and Kara

To the heights of *e*motion




# ARTIS

## TECHNICAL FEATURES

	INSTALLATION	NUMBER OF WAYS	DRIVER COMPLEMENT	SENSITIVITY 1 W / 1 m	CROSSOVER POINTS	FREQUENCY RESPONSE	NOMINAL IMPEDANCE	MINIMUM IMPEDANCE	POWER HANDLING	PEAK POWER	STANDARD FINISHES	DIMENSIONS (HxWxD) CM	WEIGHT KG
Egèa II	floorstanding	3	BC13 2 x 17 M18LB1	93.5 dB	750 - 5 200 Hz	48 - 22 000 Hz	8 ohms	3.2 ohms	100 W	700 W	1 + 2 + 3 + 4	116 x 26 x 42	30
Iroise II	floorstanding	3	BC13 2 x 21 M18LB4N	94 dB	600 - 6 300 Hz	42 - 22 000 Hz	8 ohms	3.2 ohms	120 W	840 W	1 + 2 + 3 + 4	125 x 31 x 44	36
Ambrose II	centre	3	BC13 2 x 17 M18LB1	94 dB	750 - 5 200 Hz	55 - 22 000 Hz	8 ohms	3.2 ohms	100 W	700 W	1 + 2 + 3 + 4	26 x 58 x 29	13
	bookshelf/stand wall/surround											58 x 26 x 29	
Baltic II on wall	2/7channel systems	3	TC22	93.5 dB	600 - 3 800 Hz	80 - 22 000 Hz	8 ohms	3.2 ohms	200 W	1 400 W	5 + 6 + 7	24 x 27 x 35	9
Baltic II	2/7channel systems	3	TC22	93.5 dB	600 - 3 800 Hz	80 - 22 000 Hz	8 ohms	3.2 ohms	200 W	1 400 W	8 + 9	123 x 32 x 42	16
Thor II ARTIS	active subwoofer	1	30M22	active	adjustable 40 - 180 Hz	22 - 200 Hz	active	active	250 W	750 W	8 + 9	55 x 34 x 58	24
Kara	floorstanding	4	TC22 - 30M22	93.5 dB	100/600 3 800 Hz	35 - 22 000 Hz	8 ohms	3.2 ohms	150 W	1 050 W	8 + 9	140 x 38 x 54	39
Adriatis II	floorstanding	4	TC22 - 2 x 30M22	93.5 dB	180/1 200 4 000 Hz	32 - 22 000 Hz	8 ohms	3.2 ohms	200 W	1 400 W	10	154 x 60 x 87	103

## STANDARD FINISHES



## SPEAKER TERMINALS



The new ARTIS speakers are fitted with high-end terminals enabling the use of any type of standard connector.

Kara, Iroise II, Egea II and Ambrose II can be bi-wired or bi-amped.



# Cabasse

CABASSE FRANCE  
BP 68708  
29287 Brest Cedex  
Tel: 33 2 98 41 56 56  
Fax: 33 2 98 41 21 56  
E-mail: export@cabasse.com

USA: CABASSE NORTH AMERICA  
2125, Stillwater Drive Ste. 109  
Beaumont - Texas - 77705  
Tel: 1 409 722 6727  
Fax: 1 409 722 6690  
E-mail: cabasseamerica@aol.com