



⚠ COMPONENTS MARKED WITH THIS SYMBOL HAVE CRITICAL SPECIFICATIONS IMPORTANT FOR PROTECTION FROM FIRE AND ELECTRICAL SHOCK HAZARDS. WHEN SERVICING, IT IS ESSENTIAL THAT ONLY MANUFACTURER'S SPECIFIED PARTS BE USED FOR REPLACEMENT. PRIOR TO THE RETURN OF THIS APPLIANCE TO THE CUSTOMER, AND UPON COMPLETION OF SERVICING, SERVICE PERSONNEL ARE REQUIRED TO TEST THIS UNIT FOR ADEQUATE INSULATION RESISTANCE BETWEEN THE POWER SUPPLY AND EXPOSED PARTS.

TP12	
CN2	
J3	
S1	
T1	
Q1	
U12	
CR22	
C40	
R72	
LAST USED	NOT USED
REFERENCE DESIGNATIONS	

- NOTES:
UNLESS OTHERWISE SPECIFIED:
1. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W, 5%.
 2. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS.
 3. ALL CD Z5U CAPACITORS ARE +/-20%.
 4. ALL RAD EL CAPACITORS ARE +/-20%.
 5. ▽ DENOTES GROUND IS CONNECTED TO MAIN GROUND AT ONLY ONE POINT.
 6. ▽ DENOTES GROUNDS ARE TIED TOGETHER AND CONNECTED TO MAIN GROUND AT ONLY ONE POINT.
 7. ⊕ DENOTES GROUNDS ARE TIED TOGETHER AND CONNECTED TO MAIN GROUND AT ONLY ONE POINT.
 8. +15V DENOTES VOLTAGES ARE TIED TOGETHER AND CONNECTED TO SUPPLY VOLTAGE AT ONLY ONE POINT.
 9. -15V DENOTES VOLTAGES ARE TIED TOGETHER AND CONNECTED TO SUPPLY VOLTAGE AT ONLY ONE POINT.
 10. SWITCH IS SHOWN IN THE "OUT" POSITION.
 11. REFERENCE LED BOARD PARTS LIST NO. PL360548
 12. RS IS SHOWN ON BOARD BUT IS USED AS A JUMPER.

APR 28 1967

REV	DESCRIPTION	DR	APP	DATE

APPROVAL

PRELIM	DATE	FINAL	DATE
SS			
CHECKED		CHECKED	
PROJ ENG		PROJ ENG	
CH ENG		CH ENG	
DFT MGR		RELEASED	

263X USED ON

dbx NEWTON, MA. 02195

SCHEMATIC DE-ESSER

SCALE: NONE SIZE NUMBER: C 340547 REV: 00

SHEET 1 OF 1

A

A