



**SCHEMATIC OF THE  
HEATHKIT®  
DIGITAL PROPORTIONAL SERVO**

**NOTES:**

1. ALL RESISTORS ARE 1/4 WATT. RESISTOR VALUES ARE IN OHMS (K=1000).
2. ALL CAPACITOR VALUES ARE IN  $\mu$ F UNLESS OTHERWISE MARKED.
3.  THIS SYMBOL INDICATES A POSITIVE DC VOLTAGE MEASUREMENT.
4.  THIS SYMBOL INDICATES THE NORMAL OPERATING VOLTAGE RANGE.
5. VOLTAGE ON PIN 2 OF THE IC IS VARIABLE FROM 0.2 TO 0.4, DEPENDING ON THE INPUT PULSE. VOLTAGE SHOWN IS WITH THE SERVO IN THE CENTER OF TRAVEL.
6. VOLTAGE ON PIN 6 OF THE IC IS VARIABLE FROM 1.5 TO 2.7, DEPENDING ON THE INPUT PULSE. VOLTAGE SHOWN IS WITH THE SERVO IN THE CENTER OF TRAVEL.

7. ALL VOLTAGES ARE MEASURED WITH A HIGH IMPEDANCE VOLTMETER FROM THE POINT INDICATED TO COMMON GROUND. VOLTAGES MAY VARY  $\pm 20\%$ .
8. REFER TO THE SERVO PHOTOGRAPH AND CIRCUIT BOARD X-RAY VIEW FOR THE PHYSICAL LOCATION OF PARTS.

