

# 14. SE-305

## SPECIFICATIONS

Speaker	45 $\phi$ mm (1-3/4 in) dynamic speaker
Impedance	8 $\Omega$
Matching impedance	4 to 16 $\Omega$
Frequency response	20 to 20,000 Hz
Sound pressure level	108dB/0.3V
Maximum input	500mW (each channel)
Cord length	Retractable coiled cord extensible up to 16.4 feet (5m), with 3-P plug
Weight	435g (16 oz), less cord

### NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

## PARTS LIST

Key No.	Description	Part No.
1	Head pad	SCD-434-0
2	Head band A	SNB-058-0
3	Name plate (Left)	SAL-263-0
4	Head band holder Ass'y A	SXC-077-0
5	Spring	SBH-001-0
6	Steel ball 4 $\phi$	SEF-022-0
7	Name plate (Right)	SAL-263-A
8	Head band B	SNB-059-0
9	Shaft	SXC-079-0
10	Band	SNB-060-0
11	Ear pad	SCD-431-0
12	Acoustic material	SMT-065-B
13	Speaker assembly	45-702F
14	Protection board (Right)	SNK-075-0
15	Protection board (Left)	SNK-074-0
16	Acoustic material with 20	
17	Case (Right)	SCC-231-0
18	Case (Left)	SCC-230-0
19	Coiled cord with 3-P Plug	SXC-078-0
	Operating guide	SRB-061-0
	Plastic case	SXC-073-0
	Packing case	SHG-051-0



