

6. SE-45

SPECIFICATIONS

Matching impedance	4 to 16Ω
Frequency response	20 to 20,000Hz
Maximum input	2V (each channel)
Speaker	2-3/4" (7cm) dynamic speaker with polyester cone
Control	Volume control (each channel)
Cord	Retractable coiled cord extensible up to 16.4feet (5m), with 3-P plug
Weight	14.87oz. (425g), less cord
Accessories	Y-cord

NOTE:

Specifications and the design subject to possible modification without notice due to improvements.

PARTS LIST

Key No.	Description	Part No.
1	Speaker Assembly	SXC-008-0
2	Protection Board (Left)	SXC-027-0
3	Protection Board (Right)	SXC-028-0
4	Case	SXC-023-0
5	Ear pad	SCD-134-A
6	Head pad	SCD-335-0
7	Head Band (A)	N63-741-A
8	Head Band (B)	N63-742-A
9	Adjusting Knob (Left & Right)	SXC-026-0
10	Coiled cord with 3-P Plug	SXC-015-0
11	Lead Wire	SXC-019-0
12	Band Shaft	SXC-006-0
13	Knob	SXC-037-0
14	Volume Control	C81-620-B
	Packing Case	H93-634-0
	Y-Cord	D53-639-0
	Operating Guide	SRB-013-0



